



# Development of a Cloud Particle Sensor (CPS) for radiosonde sounding

Masatomo Fujiwara<sup>1</sup>, T. Sugidachi<sup>1,2</sup>, T. Arai<sup>1</sup>,

K. Shimizu<sup>2</sup>, M. Hayashi<sup>3</sup>, Y. Noma<sup>3</sup>, H. Kawagita<sup>3</sup>, K. Sagara<sup>3</sup>, T. Nakagawa<sup>4</sup>, S. Okumura<sup>4</sup>,  
Y. Inai<sup>5</sup>, T. Shibata<sup>6</sup>, S. Iwasaki<sup>7</sup>, and A. Shimizu<sup>8</sup>

<sup>1</sup>Hokkaido Univ., Japan; <sup>2</sup>Meisei Electric Co., Ltd.; <sup>3</sup>Shinyei Technology Co., Ltd.; <sup>4</sup>Shinyei K.; <sup>5</sup>Tohoku Univ.; <sup>6</sup>Nagoya Univ.; <sup>7</sup>NDA; <sup>8</sup>NIES



(Biak, Indonesia)

# Introduction



- Clouds play various roles in the weather and climate . . . through latent heat transport, precipitation and the hydrological cycle, and shortwave and longwave radiative processes.
- There are several in situ cloud microphysical sensors for aircraft and weather balloon platforms.
- Balloon sensors include: **NCAR Formvar replicator**, **HYVIS** (Hydrometer Video-Sonde, JMA-MRI/Meisei), **Videosonde** (Kyushu Univ./Yamaguchi Univ., Japan), **Backscattersonde**, **COBALD** (Compact Optical Back- scatter Aerosol Detector, ETH), etc.
- The masses of these balloon-borne particle instruments range from 1 to 6 kg, except for COBALD whose mass is 500 g.
- A cloud particle instrument of similar mass (and cost) to radiosondes would be useful for e.g., cloud sciences, radiosonde RH sensor validation, etc.
- Shinyei Technology Co. Ltd., Japan, has several particle sensors, including a compact, light, and low-cost optical pollen sensor **PS2**.
- Based on this PS2, with an interface to Meisei RS-06G or RS-11G radiosondes, a balloon-borne small mass (~200 g) cloud sensor called the **Cloud Particle Sensor (CPS)** has been developed.



Two PS2 instruments in an instrument shelter.  
<http://www.shinyei.co.jp/stc/eng/>

# Instrumentation (1)

- Particles are introduced into the detection area in CPS using balloon ascent/descent motion:
  - A diode laser: Source of linearly polarized light at  $\sim 790$  nm.
  - Two photo detectors: Silicon photo diodes, placed at angles of 55 deg. (detector #1) and 125 deg. (detector #2) with respect to the source-light direction. A polarization plate is placed in front of detector #2.
  - Detection area: Roughly  $\sim 1$  cm x 1 cm (horizontally) x  $\sim 0.5$  cm (vertically). Thus, its volume is  $\sim 0.5$  cm<sup>3</sup>.
- A particle that passes through the detection area scatters the laser light, and the two detectors receive the scattered light signal and thus count that particle.







# Instrumentation (2)



- The degree of polarization (**DOP**) is defined, to characterize the phase of the cloud particle, as:  

$$DOP = (I_{55} - I_{125p}) / (I_{55} + I_{125p})$$
- DOP should be close to unity for spherical (i.e. liquid) particles (as  $I_{125p} = \sim 0$ ), while DOP would take various values between  $-1$  and  $+1$  for non-spherical ice crystals.
- The original measurement is **number of particles counted per second**. It can be converted to **number concentration** if the flow speed in the detection area is known/inferred.
- Upper limit for the number concentration & a proposed partial correction of the number of particles:
  - The volume of the detection area is non-zero and estimated as  $\sim 0.5 \text{ cm}^3$ .
  - If there are 2 particles or more, CPS cannot count particles correctly – thus, the upper limit would be  $\sim 2 \text{ cm}^{-3}$ .
  - Particle signal width** (in milli-second) is also monitored, which can be used to infer the degree of particle overlapping.




# Laboratory experiments

- Various types of **standard spherical particles** were used
  - (1) to determine the lower detection limit and the relationship between the  $I_{55}$  value and the water/ice diameter,
  - (2) to investigate the DOP distributions for spherical (thus water) particles
- (Mie scattering theory was used to convert the diameters of the standard spherical particles to those of spherical water droplets and those of hypothetical spherical ice particles.)
- The CPS was unable to detect 1  $\mu\text{m}$  diameter polystyrene particles but could **detect 2  $\mu\text{m}$  diameter** borosilicate glass particles.




- Standard spherical particles are: polystyrene (1  $\mu\text{m}$ ), borosilicate glass (2, 5, 10, and 20  $\mu\text{m}$ ), and soda lime glass (30, 60, and 100  $\mu\text{m}$ ).
- ~1000 to ~8000 particles were used for each type.

# Flight results (1/2) Mid-latitude site Moriya, Japan, 17:30 LT, 21 January 2015



(d) DOP:  
This suggests that the clouds at 1–4.5 km were in **mixed phase** where water and ice clouds co-existed.

# Flight Results (2/2) Tropical site Biak Indonesia, 18:00 LT, 27 February 2015



(RH from CFH is also  
shown (in red).)

# Summary and future plans

- CPS is a small-mass ( $\sim 200$  g) optical particle counter for radiosounding (currently with Meisei radiosondes).
- Lower limit of the particle size is  $\sim 2$   $\mu\text{m}$ ; capable of ice/liquid water distinction; upper limit of number concentration is  $\sim 2$   $\text{cm}^{-3}$ , with a proposed correction algorithm.
- (Because of the near-IR light measurements, day-time soundings need some special considerations.)
- Possible scientific applications include:
  - cirrus cloud processes in the upper troposphere
  - radiosonde RH sensor validation e.g., during radiosonde intercomparison campaigns
  - applications for dropsonde systems, long-duration balloon systems, etc.
- Intercomparisons with other, well-characterized cloud particle instruments are necessary for the uncertainty quantification for (corrected) number concentration measurements.
- Reference: Fujiwara, M., Sugidachi, T., Arai, T., Shimizu, K., Hayashi, M., Noma, Y., Kawagita, H., Sagara, K., Nakagawa, T., Okumura, S., Inai, Y., Shibata, T., Iwasaki, S., and Shimizu, A.: Development of a cloud particle sensor for radiosonde sounding, *Atmos. Meas. Tech.*, **9**, 5911-5931, doi: 10.5194/amt-9-5911-2016, 2016.  
[<http://doi.org/10.5194/amt-9-5911-2016>]
  - Four flight results (including the two cases in previous slides) are shown and discussed in detail in this paper!
- During 2016-2018, several flights have been made in Japan (with HYVIS), India (including BATAL project), and Tarawa (Kiribati; SOWER).
- Currently, Version 2/3 of the CPS is being developed, aiming at the use in dropsonde systems.