

# THE MODEM SONDE DATA PRODUCT

## PROGRESS AND PLANS

S. Evan, JP. Cammas, V. Duflot, F. Posny (LACy)  
M. Haeffelin, J. Badosa, JC. Dupont, V. Van  
Aalderen (IPSL)  
G. Clain, C. Raux, P. Charpentier (MODEM),  
F. Marin, F. Besson (Météo-France)



# ***Outline***

1. Measurement compensations and uncertainties
  - RH sensor temperature bias at high altitude
  - Robotsonde effect at low altitude
  - Comparisons with RS92
2. GRUAN M10 ground-check procedure
3. GRUAN M10 Robotsonde operations
4. GRUAN M10 data processing and Documentation
5. Future activities 2017-2018

# ***Relative Humidity compensations and uncertainties***

## Principle:


- Capacitive sensor
- Oscillation frequency of the sensor is measured by a microcontroller
- Capacitor frequency varies with temperature

## Calibration:

- Oscillation frequency at 55% RH

New corrections: accounting for temperature differences between Air and RH capacitive sensor

1. Induce a dry bias at high altitude
2. Induce a dry bias at very low altitude (robotsonde)




**M10**



# ***High-altitude heating effect (dry bias)***

## Compensation at NIGHT : statistical approach

- New compensation based on mean ( $T_{\text{capacitor}} - T_{\text{air}}$ ) model as a function of height and Air temperature at NIGHT
- At NIGHT :  $T_{\text{air}}$ : 0 to  $-80^{\circ}\text{C}$ ;  $\Delta T$ :  $1\text{-}2^{\circ}\text{C} \rightarrow \text{RH} \times 1.05 - 1.5$




**Heating effect of capacity sensor well quantified  
Compensation law developed to correct dry bias**

# ***High-altitude heating effect (dry bias)***

Compensation during DAY: statistical approach

- New compensation based on mean ( $T_{\text{capacitor}} - T_{\text{air}}$ ) model as a function of height and Air temperature during DAY
- During DAY :  $T_{\text{air}}$ : 0 to -80°C;  $\Delta T$ : 1-10°C  $\rightarrow$  RH x 1.05 – 2.0




**Heating effect of capacity sensor well quantified**  
**Compensation law developed to correct dry bias**

# High-altitude heating effect (dry bias)

## Compensation during DAY: statistical approach

- Compensation law applied to correct dry bias
- Dry bias is around 16% at 10km






# ***Very-low-altitude effect (dry/moist bias)***


## Impact of robotsonde launch on very low altitude RH:

- Météo-France uses Robotsonde since April 2015;
- Temperature controller inside shelter induces  $T_{\text{capacitor}}$  difference with outside Air temperature during ~150m meters.
- Compensation law applied to correct low-altitude humidity bias

***( $T_{\text{capacitor}} - T_{\text{air}}$ ) for 365 day time soundings at Trappes (Jan. – Dec. 2014)***



***( $T_{\text{capacitor}} - T_{\text{air}}$ ) for 365 day time soundings at Trappes (Jan. – Dec. 2016)***




**A compensation law must be applied at very low altitude**

# ***Very-low-altitude effect (dry/moist bias)***

## Impact of robotsonde launch on Relative Humidity.

- Observed (mostly) dry bias due to  $T_{\text{capacitor}}$  higher than  $T_{\text{air}}$
- Correction of dry bias will be implemented in GRUAN code

*( $RH_z - RH_{200m}$ ) versus  $T_{\text{air}}$  for 365 night time soundings at Trappes (Jan. – Dec. 2016)*



**MODEM compensation law corrects the very low altitude bias**



# Comparison with RS92 radiosondes



## Analysis of M10+RS92 simultaneous RS

- 7 M10+RS92 launches done at SIRTA
- RH compensations have been tested to better understand and document the current corrections for GRUAN procedures.
- Complete methodology for GRUAN procedures has been tested (raw M10 data + metadata, GRUAN algorithm, level 1 GRUAN products)

11/10/2016



14/10/2016



# GRUAN M10 ground-check

2-step ground-check (about 10 min per sonde for data acquisition):






Comparison with calibrated  
temperature and RH sensors in  
ventilated hut – ambient conditions



RH measurement in saturated  
environment using SHC1

# GRUAN M10 Robotsonde operations


- Each sonde goes through GRUAN ground-check and is then loaded in the carousel
- Robotsonde records ground-check and metadata



15 robotsondes in operation in the world

# GRUAN – M10 RobotSonde Protocol

GRUAN M10 RobotSonde specifics:





# M10/CFH sondes in La Réunion


- Launches with CFH+M10 started in Nov 2014 at the Maïdo Observatory, since then 12 Launches with CFH+M10 (some of them include RS92)

Nov 2014  
TNA-ACTRIS  
1CFH+M10+RS92


May 2015  
MORGANE campaign  
4 CFH+M10+RS92

Jan/Mar 2016  
HAIC campaign  
+ TNA ACTRIS  
2 CFH+M10

Mar/May 2017  
TC Enawo  
+ TNA ACTRIS  
5 CFH+M10




Climatological RH mean



from Damien Héron


4 “Summer” profiles +  
8 profiles for May conditions

# ***M10 comparisons with CFH: Summer conditions***






# ***M10 comparisons with CFH: May conditions***



Dry bias above 10km observed for all May Profiles

# M10 comparisons with CFH



Difference between capacitor temperature and air temperature explains the dry bias, should be reduced by applying GRUAN M10 corrections

# ***GRUAN M10 data processing and documentation***

- Ground check data and M10 metadata collected by Robotsonde → Metadata file
- RS profile data provided as “RAW M10” data file
- After the flight, Metadata + RAW datafiles sent by Météo-France to IPSL
- Specific GRUAN Python code converts RAW M10 data → GRUAN M10 data
- Metadata + GRUAN M10 data files → GRUAN data archive through RSLaunch client

## ***Documentation***

- Capacity sensor for RH measurements: description, corrections & uncertainties
- Thermistor for T measurements: detailed description, corrections & uncertainties
- Python code for M10 processing documentation
- *Badosa et al. M10 relative humidity measurements: description, corrections & uncertainties. Still in prep.*

## ***Future activities 2017-2018***

- Finalize procedures for M10 data processing and apply corrections for tropical conditions using La Réunion dataset of M10/CFH/RS92
  - Implement GRUAN procedure at la Réunion for weekly NDACC/SHADOZ ozone sounding
  - Meteo-France in La Réunion will start using the robotsonde in 2018.
- 
- IOP at SIRTAsite Sept. 2017 to compare RS92/RS41 and M10, and validate dry bias compensation law.
  - Finalize data transfer with GRUAN algorithm until IPSL server
  - Start weekly RS with GRUAN procedures at Trappes Meteo-France site using robotsonde.